


FATH + flowsort



X-FLOW 90 90° TRANSFER UNIT

Flexible and robust solution for every conveyor system



ROBUST FRAME

To ensure durability and stability



SPECIAL BELT

Our belts are made of a special, anti-slip composite material and are internally guided to ensure the belts do not jump off the rollers



MODULAR

Standard modules that fit into every conveyor system



SHORT LEAD TIME

Get your product in just 6 weeks!

FATH

flow-sort

X-FLOW 90

A unique design for transferring products at a 90° angle



PRODUCT INFORMATION

Standard width
Module height
Module length
Diverting angle

SORTING INFORMATION

Maximum sorting capacity
Minimum parcel dimension
Maximum parcel width
Maximum load

CONTROL

Motor drive for lift
Motor drive for transport belt
Maximum speed

PRODUCT SPECIFICATIONS

X-FLOW 90

90° transfer unit

400 - 420 - 600 - 620, up to 820 mm
150 mm (underneath the conveyor frame)
702 mm & 847 mm
-90° & +90°

1200 pph
150 mm x 150 mm
820 mm
35 kg

24V Pulse Gear Drive
24V Pulse Gear Drive
0.41 m/s



X-Flow 90

CONTACT US

+31 [0]85-0761339

info@flow-sort.com

www.flow-sort.com